

XPEL PRIME™

XR PLUS adatlap



Termék	Vastagság	Látható Fény			NAPENERGIA			UV Szűrés	Tükröződés Csökkenés	Árnyékolási Együttható	IR Szűrés (780-1700 nm)	IR Szűrés (900-1000 nm)
		Áteresztés VLT	Tükrözés VLR	TSER	Áteresztés	Tükrözés	Elyelés					
XR PLUS 5	1.5 Mil	5%	6%	71%	4%	6%	90%	99%	95%	0.34	98%	98%
XR PLUS 15	1.5 Mil	12%	6%	69%	7%	6%	87%	99%	88%	0.36	97%	97%
XR PLUS 20	1.5 Mil	18%	7%	66%	10%	6%	84%	99%	80%	0.39	97%	97%
XR PLUS 30	1.5 Mil	31%	7%	61%	17%	6%	77%	99%	66%	0.44	96%	97%
XR PLUS 35	1.5 Mil	38%	7%	59%	20%	6%	74%	99%	58%	0.47	96%	97%
XR PLUS 45	1.5 Mil	45%	7%	58%	22%	6%	72%	99%	51%	0.48	97%	97%
XR PLUS 55	1.5 Mil	57%	8%	53%	29%	6%	65%	99%	37%	0.54	97%	97%
XR PLUS 70	2 Mil	67%	9%	52%	35%	7%	58%	99%	27%	0.59	92%	94%